



## KEY FEATURES:

- UN/DOT compliant with UN marking
- 10 Gauge, 304 stainless steel with 2B finish
- One piece body and single seam welding
- Sloped bottom for virtual 100% discharged
- 22-5/16" (566mm) Top manway with EPDM Gasket & Bolted Clamp Ring
- 3" Fusible cap with Lanyard
- 2" (50.8mm) Top bung fitting with EPDM Gasket
- Stainless Steel UNTAG
- Heavy Duty lifting lugs / Stackable like positioners
- 2" (50.8mm) discharged assembly with 316 Stainless Steel piece elbow, locking handle ball valve and plastic plug
- Full-length valve guard on side drain tanks
- 6-1/2" (height)(166mm) radius corner legs with Caps (9-1/4"(235mm) on center drain tanks)
- 3-way forklift entry one side drain tanks
- TD Energy Stainless Steel Tote Tanks IBS'C are rated UN31A for the Transportation & Storage of hazardous and non-hazardous liquid chemicals
- Tote Tanks are used for a variety of applications including: Combustible & Flammable raw materials, Solvents & Solvent based chemical preparation, Water Treatment Chemicals, Oil & Water based Lubricants, Downhole Chemicals, Paints & Allied Products, Resins, Pigments & Dyes, Cleaning & Sanitation Chemical, Pharmaceutical & Food Preparation, Industrial Organics.

- Optional Slings: DNV2.7-1 Certified

ITEM		
<b>External Dimension Frame</b>	<b>Length (mm)</b>	<b>1,500</b>
	<b>Width (mm)</b>	<b>1,160</b>
	<b>Height (mm)</b>	<b>2,340</b>
<b>External Dimension Tank</b>	<b>Length (mm)</b>	<b>1,257</b>
	<b>Width (mm)</b>	<b>1,105</b>
	<b>Height (mm)</b>	<b>1,924</b>
<b>Grow Weight (kg)</b>		<b>5,000</b>
<b>Tare Weight (kg)</b>		<b>580</b>
<b>Max Payload (kg)</b>		<b>4,420</b>
<b>Nominal Capacity (Litres)</b>		<b>2,082</b>
<b>Max Load Capacity (Litres)</b>		<b>2,040</b>